

# A Comparative Assessment of similar Experiments by means of CFD

## - Buoyancy Driven Mixing Processes

Stephan Kelm, Wilfried Jahn, \*Jan Lehmkuhl, \*Hans-Josef Allelein

\*Institute for Reactor Safety and Technology, RWTH Aachen University

*European Review Meeting on Severe Accident Research  
Marseille, France, March 24 – 26, 2015*

Supported by:



Federal Ministry  
for Economic Affairs  
and Energy


on the basis of a decision  
by the German Bundestag

**Project No. 150 1407**

## Outline


- Background & Strategy
- Comparative Simulations
  - *Data Basis*
  - *Modeling Approach*
  - *Results*
- Summary & Conclusions

## Simulation Task – Predicting Hydrogen Risk during SA




## H<sub>2</sub> Transport & Mixing Inside Containment Compartments

- Are driven by pressure and density differences
- Categorize validation series:



- Identical modeling approach,
- 2 simulations, one 'blind' with specified one 'open' with measured IC's & BC's

## Test Series 2.1 – Global Natural Circulation Mixing




## „Standard“ CFD Model – Physics

- U-RANS, total energy and species transport equations
- k- $\omega$ -SST model
  - incl. buoyancy turbulence production und dissipation  
 $Sc_t = 0.9$ ,  $Pr_t = 0.9$
- ideal gas equation of state
- temperature dependent fluid properties
- thermal radiation
  - Monte Carlo, 200.000 histories,  
participating media:  $\alpha_{\text{steam}} = 1.0$ ,  $a_{\text{Air/He/H}_2} = 0$ ,  
 $\varepsilon_{\text{Wall}} = 0.6$ ,  $\varepsilon_{\text{adiabatic}} = 0$  (reflecting)
- walls:
  - automatic wall treatment
  - conjugate heat transfer
  - thermal BC:  $T_{\text{sec}} + \text{HTC}$




## Numerical Grids - MISTRA & THAI




- Refinement close to the heated/cooled walls and at the mixing zone / layer
- Low aspect ratios where flow is 3D
- Grid independency investigated

## Results NATHCO (idealized conditions)







## NATHCO – Thermal Initialization




## Results NATHCO (real test conditions)




## NATHCO – Effect of the Thermal Initialization



## TH22 experimental transient („best“ result)



## Ergebnisse TH22 (ideal conditions)



- Different phenomenology / mixing mechanism in simulation
- Significantly overestimated mixing time
- Deficiency in the basic physical models or missing experimental characteristic?




## TH22 – Revision of IC & BC

### Improved thermal boundary conditions

- Heated / cooled walls:
  - *Temperature + HTC instead of fixed temperature*
  - ✓ *Heat fluxes checked*
- Other structures (heat sinks):
  - ✓ *Temperature checked*
  - *Visible effect of radiation model*


### Improved initial helium distribution:

- *2D inlet boundary instead of volumetric point source*
  - *Impact on initial helium distribution*
  - *Low effect on other variables ( $u, v, w, T, k, \omega$ )*






## Ergebnisse TH22 (real conditions)



## TH22 – Effect of IC and BC



## Test Series 2.1 – Summary & Conclusions (1)



CFD can predict complex 3D natural circulation driven flows and mixing processes

However, CFD is a boundary value problem, i.e.:

- Avoid definition of fixed wall temperatures or fixed heat fluxes and limit both by the definition of an external temperature and HTC
- Avoid wall functions and use a fine boundary layer resolution to predict correct gas-wall heat transfer
- Specify the initial structure temperature field consistent to the test (structures represent local heat sinks and thermal inertia).
- Consider thermal (gas) radiation for a consistent prediction of internal structure temperatures and gas-wall heat transfer




Single minor model simplifications (user decisions) may multiply up to a significant effect on the transient duration and phenomenology.


## Test Series 2.1 – Summary & Conclusions (2)

For model validation:

- No experimental characterization of the flow field and mixing mechanism available
- Detailed validation of the heat balance and temperature field necessary
- Make use of all available measurements  
In-house development of an 'import filter'  
for exp. data in CFX (Pre & Post)



**PANDA ST1\_2 test: Temperature map provided by PSI vs. simulation**




## Test Series 2.1 – Summary & Conclusions (3)

For the simulation of containment flows:

- ✓ The consistent prediction of test cases indicate that there are no important physics missing in the 'standard' model
- Need for a reliable estimate of initial (non-uniform) structure temperatures in particular if only a time window of the transient is analyzed
- Need to consider all structures thermal inertia (distributed heat sinks) and flow resistance
- It is impossible to define a conservative treatment for the initial (concrete) structure temperature field



Strong 'user-effect' possible. Need for a common approach & 'Best Practise Guideline'



GRS, 2014



## Acknowledgements

The continued development of CFD models for prediction of H<sub>2</sub> mixing and mitigation is performed in close cooperation with RWTH Aachen University and funded by German Federal Ministry of Economic Affairs and Energy (Project No. **1501407**)

Supported by:



on the basis of a decision  
by the German Bundestag

Special thanks to the experimental teams for their efforts in conducting and documenting the test series. We acknowledge the support of the different funding bodies.



Supported by:

énergie atomique • énergies alternatives



on the basis of a decision  
by the German Bundestag