

Experimental Investigations on the Coolability of Stratified Debris Beds

S. Leininger, R. Kulenovic and E. Laurien

University of Stuttgart
Institute of Nuclear Technology and Energy Systems (IKE)

Pfaffenwaldring 31
70569 Stuttgart, Germany

Email of corresponding author: simon.leininger@ike.uni-stuttgart.de




Outline

- Motivation
- Aim of Work
- DEBRIS Facility
- Determination of Heat Input
- Boiling Experiments
- Dryout Experiments
- Conclusion

Motivation

Loss of coolant scenario:

- Over heating of fuel elements due to emerging decay heat
- Melting of the core and relocation to the lower plenum
- Fragmentation and formation of a particle bed due to the presence of water
- Remelting due to insufficient heat removal
- Possible melting of the RPV
- Relocation of core material to the reactor pit and again formation of a particle bed




Aim of Work

- In general: Providing data for numerical model development and validation
- In specific: Effect of a stratification in terms of heat input and permeability on the coolability

DEBRIS Facility

Design parameters:

- $P_{\max} = 4 \text{ Mpa}$
- $T_{\max} = 250 \text{ }^{\circ}\text{C}$
- volumetric, inductive heating
($P_{\text{el}} = 140 \text{ kW}$, $f_{\text{rf}} = 300 \text{ kHz}$)



DEBRIS Facility


Cylinders 3x5.75 mm
Stainless steel
 $d_{p,eff} = 2.5 \text{ mm}$
 $\varepsilon = 0.38$



Screws M3x10, ISO 1207
Standard steel
 $d_{p,eff} = 2.8 \text{ mm}$
 $\varepsilon = 0.58$



Influence of non-spherical (well-defined geometry) particles
on debris coolability \leftrightarrow spherical particles?



Determination of Heat Input

Determination of heat input in a range of 30 - 40 °C for different generator levels:


$$Q = \left[\varepsilon \cdot \rho_w \cdot c_p^w + (1 - \varepsilon) \cdot \rho_s \cdot c_p^s \right] \frac{dT}{dt} \quad q = Q \cdot h$$

Calculation of gas superficial velocity J_g :

$$J_g = \frac{q \cdot A - (T_s - T_{in}) \cdot \dot{m} \cdot c_p^w}{A \cdot \Delta h_v \cdot \rho_g}$$







Screws are made of standard steel
to have a better coupling to the
electro-magnetic field

Different particle materials
→ different heat input curves







Bed Configurations

Homogeneous and stratified beds

Bed no.	1	2	3	4	5	6
Stratification	no (homogeneous beds)		axial		azimuthal	radial
Geometry						
Ceramic particles						
Cylinders						
Screws						
Composition (Vol. %)	Cylinders (100 %)	Screws (100 %)	Screws (80 %), Cylinders (20 %)	Screws (96 %), Cylinders (4 %)	Screws (50 %), Cylinders (50 %)	Screws (90 %), Cylinders (10 %)


Boiling behaviour of homogeneous beds



Flow rate in the natural circulation loop



Axial Stratification 80/20

- Strong dependence of flow rate in the natural circulation loop on the total axial pressure difference dp_8
- High pressure \rightarrow high steam density \rightarrow low friction \rightarrow high flow rate \rightarrow better coolability
- Turning points are moving to higher q with increasing pressure



Dryout Experiments – Cylinders



Cylinders, 0.1 MPa, $J_1^0 = 0$ mm/s (Top-Flooding)



Dryout Experiments – Stratified Bed

Azimuthal Stratified Bed, 0.5 MPa,


$J_1^0 = 0$ mm/s (Top-Flooding)



“Plateau” Behaviour


“Normal” Behaviour

- Rapid temperature increase at DHF, e. g. for bed 2, screws, top-flooding, 3 bar




“Plateau” Behaviour

- No rapid temperature excursion, coolable at a higher temperature level, e. g. for bed 5, azimuthal stratification, top-flooding, 3 bar




Dryout Experiments – Top-Flooding



- Highest DHF for screws (high porosity, $\varepsilon = 0.58$), lowest DHF for cylinders (low porosity, $\varepsilon = 0.38$)
- Strong reduction of DHF due to axial stratification
- Plateau behaviour for azimuthally stratified bed (remaining at temperature level above saturation temperature instead of rapid temperature increase)

Dryout Experiments – Bottom-Flooding (Natural Circulation Loop)



- Flow rate in the downcomer limited by strong fluctuations of the water level for bed 2 (screws) and bed 5 (azimuthal), thus no DHF can be determined
- For some experiments not sufficient heat input to reach dryout at 5 bar

Conclusions

- Boiling and dryout experiments carried out for two homogeneous beds and four stratified beds with strongly different porosity ($\varepsilon = 0.38$ vs. 0.58)
- Good qualitative agreement of flow rate in the natural circulation loop with measured axial pressure difference
- No significant cross flow detected for the azimuthally stratified bed
- Plateau behaviour in dryout experiments for stratified bed
- Strong increase of DHF by bottom-flooding compared to top-flooding
- Strong decrease of DHF even by a thin layer with low permeability on top of the bed

Acknowledgement

Thank you for your attention!

German Federal Ministry of Economic Affairs
and Energy (project no. 1501466)

Supported by:



Federal Ministry
for Economic Affairs
and Energy

on the basis of a decision
by the German Bundestag